



UZIN PE 460

2-COMPONENT EPOXY BLOCKING PRIMER

ENVIRONMENTAL LABELING



EMICODE EC 1 PLUS -
Very low emission



French VOC A+ classification



M1 classified

ENVIRONMENTAL PRODUCT DECLARATIONS (EPD)*

- ☐ Product-specific EPD
- ☒ European Model EPD
- ☐ No EPD available



* The detailed life cycle calculation in form of an EPD can be found in a separate document

PRODUCT INFORMATION

Product Carbon Footprint	3,80 kg CO ₂ e/kg	CO ₂ footprint (incl. biogenic C) calculated from cradle to gate CO ₂ footprint comes from the assigned EPD
GISCODE	RE90	Epoxy resin products, CMR characteristics

UZIN PE 460

2-COMPONENT EPOXY BLOCKING PRIMER



SUSTAINABLE BUILDING CERTIFICATIONS

If this confirmation is not sufficient, you are welcome to request declarations for your individual building project.

DGNB



German Sustainable Building Council (DGNB)

DGNB criterion ENV 1.2 Risks for the local environment

Product group 9 Barrier coats, screed resins, waterproofing under tiles

Quality level: QS 4

QNG



Quality Seal for Sustainable Buildings (QNG)

Product group 3.1 Flooring materials

Quality level: QNG suitable

BNB



Assessment system for sustainable building (BNB)

Product group 10b Flooring materials

Quality level: QS 3

BREEAM



BREEAM: HEA 02 Indoor air quality

Product group "Interior adhesives and sealants (including flooring adhesives)"

Quality level: BREEAM suitable

LEED



LEED requirements in IEQ Credit (4.1)

Low Emitting Materials (LEED v4)

VOC content according to SCAQMD Rule 1168

Quality level: <50 g/L